

ExxonMobil

Refining and Supply Company
22777 Springwoods Village Parkway,
Spring, TX 77389

IBP, F	19.1	60.9	166.0	330.7	480.9	651.5	1,001.3	
5 vol%, F	149.3	68.4	174.9	337.5	488.8	664.9	1,013.2	
10 vol%, F	208.9	73.6	184.1	345.0	497.6	679.9	1,026.9	
20 vol%, F	311.1	84.2	201.2	360.0	515.0	710.4	1,055.6	
30 vol%, F	417.2	101.4	217.3	375.1	532.3	741.7	1,086.7	
40 vol%, F	521.7	109.1	233.1	390.1	549.4	773.8	1,120.6	
50 vol%, F	621.1	126.9	248.9	405.2	566.3	807.0	1,158.2	
60 vol%, F	720.9	136.0	264.7	420.3	583.2	841.4	1,200.6	
70 vol%, F	829.4	144.2	280.8	435.3	599.9	877.3	1,249.6	
80 vol%, F	954.4	151.7	297.1	450.3	616.6	915.2	1,308.3	
90 vol%, F	1,123.4	158.6	313.5	465.2	633.3	955.7	1,382.8	
95 vol%, F	1,251.7	161.8	321.7	472.6	641.6	977.3	1,430.6	
EP, F	1,454.3	164.7	329.2	479.3	649.2	997.7	1,502.0	
Freeze point, F			(105.3)	(52.0)	21.9			
Smoke point, mm			30.8	23.8	16.2			
Naphthalenes (D1840), vol%				1.7	7.8			
Viscosity at 100C/212F, cSt	2.6	0.3	0.3	0.4	0.7	1.5	7.1	2,244.9
Viscosity at 150C/302F, cSt	1.5	0.2	0.3	0.3	0.5	0.9	2.7	135.3
Cetane Index 1990 (D4737),				29.4	41.3	53.3		
Cloud point, F				(114.4)	(63.4)	15.2		
Aniline pt, F					140.5	164.6	192.0	